



Gate Automation Systems (Irl.)

Locall: 1890 74 75 76 **Tel:** +353 65 6841175 **Fax:** +353 65 23639

Email: sfe@eircom.net **Web:** www.automationgate.com

Personal Car Parking Systems – Range 3

Compact automation that safeguards your own car place. Uses easy to replace breaking element useful to limit the damages in case of accidental impact. Uses simple wiring. Fast installation and emergency key release make it a safe and versatile product with outstanding performance.

Versions

MANUAL

- Feed: V D.C. 24
- Motor absorption: max. 2A
- Motor rating: W25
- Working intermittence: 80%
- Protection: IP54
- 90° rotation time: 9"
- Weight: 7.5kg



AUTOMATIC WITH BATTERY

- completely independent unit (doesn't need connection to the main power supply)
- remote controlled through a control panel which can control up to 4 units
- Dimensions when open: W403 x L513 x H453
- Dimensions when closed: W403 x L513 x H98
- Opening time: 5sec.
- Anticrushing system: 3kg
- Working temp.: -10° to +40° Celsius
- Weight resistance: 1,800kg
- Motor insulation class: IP56
- Control unit insulation class: IP56
- Transmitter range: 20 metres
- Battery: 6V cc 6 Ah re-chargeable Pb
- Autonomy: 8 months with 4 operations per day



I.S. EN 50133-1:1997

Brought to you by Gate Automation Systems (Irl)





- Materials: Zinc plated iron + painted 3mm
- Absorbed power without load: 360 μ A
- Absorbed power with load: 500mA

Wireless/ Battery



- Dimensions open:
W403 X L513 X H453
- Dimensions closed:
W403 X L513 X H98
- Opening time: 5 sec.
- Transmitter range: 20 metres
- 6V cc 6Ah re-chargeable
Pb battery
- Zinc plated iron + painted 3mm

