



## Gate Automation Systems (Irl)

Locall: 1890 74 75 76 Tel: +353 65 6841175 Fax: +353 65 23639

Email: [sfe@eircom.net](mailto:sfe@eircom.net) Web: [www.automationgate.com](http://www.automationgate.com)

### Metropole Bollard Range

#### (A) METROPOLE bollard with 3000 Joules resistance

An access control system integrating 4 electrical bollards in steel with painting in RAL code and electronic command in an outdoor cabinet.

Dimensions: 600mm high x 285mm diameter



Benefits:

- Electrical bollard is easier to install and to maintain  
In case of power shortage, the bollard will go down (positive safety)  
The bollard is equipped with shredding screws. In case of shock exceeding 3000 joules, the bollard head will shred from the motor.
- The motor will remain undamaged inside the housing under the earth level.
- The bollard head has no mechanism inside.
- The repair will consist of new screws to fix the bollard head back on the motor.

#### (B) METROPOLE bollard with 30 000 joules resistance

An access control system integrating 4 electrical security bollards in steel with painting in RAL code and electronic command in an outdoor cabinet. The 30,000 Joules bollard from SAGEM resist to shock with cars and remain functional when the shocks is below 30,000 Joules.

Dimensions: 600mm high x 285mm diameter