



**Locall:** 1890 74 75 76    **Tel:** +353 65 6841175    **Fax:** +353 65 23639  
**Email:** [sfe@eircom.net](mailto:sfe@eircom.net)    **Web:** [www.automationgate.com](http://www.automationgate.com)

## Cylinder Automatic Bollard - Generation 6

The Generation 6 Line Retractable bollards comply with France's NF P 98.310 standard and are composed of 3 cast structural parts only, which do not wear: the casing, the bollard head and the cover. White reflective tape as standard applied.

### Features

#### Motorization: Electro-pneumatic

- Compressed low-pressure air
- Several bollards can be operated from the same technical centre (one single electric motor = several access points)
- Distance between technical centres/ bollards = up to 800m/ 875 yds
- Environmentally friendly (ISO 14 001 standard)
- Fast motion, lowering and rising of bollard are independently adjustable
- No damage to bollard if vehicle drives over it while it is in motion

#### Dimensions Available

- 500mm high x 120mm diameter
- 500mm high x 200mm diameter
- 500mm high x 250mm diameter
- 750mm high x 120mm diameter
- 750mm high x 200mm diameter
- 750mm high x 250mm diameter

#### Material

- Cast Steel

#### Finish

- Zinc coating and powder coated finish available in 6 RAL colours

#### Optional Extras

- Upper limit switch
- Antifreeze heater



Brought to you by Gate Automation Systems (Irl.)



# Gate Automation Systems (Irl)

**Locall:** 1890 74 75 76    **Tel:** +353 65 6841175    **Fax:** +353 65 23639  
**Email:** [sfe@eircom.net](mailto:sfe@eircom.net)    **Web:** [www.automationgate.com](http://www.automationgate.com)

## Cylinder Automatic Bollard - Generation 6 High Security Range

The Generation 6 Line Retractable bollards comply with France's NF P 98.310 standard and are composed of 3 cast structural parts only, which do not wear: the casing, the bollard head and the cover. The thickness of the steel walls is up to 20mm. Double cover increases shock resistance even in the upward position. A portion of the bollard remains held by the two covers that are more than 250mm long.

### Features

#### Motorization: Electro-pneumatic


- Compressed low-pressure air
- Several bollards can be operated from the same technical centre (one single electric motor = several access points)
- Distance between technical centres/ bollards = up to 800m/ 875 yds
- Environmentally friendly (ISO 14 001 standard)
- Fast motion, lowering and rising of bollard are independently adjustable
- No damage to bollard if vehicle drives over it while it is in motion
- Hydraulic model available on request

#### Dimensions Available and Materials

- 700mm high x 250mm diameter.....Steel
- 900mm high x 250mm diameter.....Steel

#### Finish

- Zinc coating and powder coated finish available in 6 RAL colours



Brought to you by Gate Automation Systems (Irl.)





# Gate Automation Systems (Irl)

**Locall:** 1890 74 75 76    **Tel:** +353 65 6841175    **Fax:** +353 65 23639  
**Email:** [sfe@eircom.net](mailto:sfe@eircom.net)    **Web:** [www.automationgate.com](http://www.automationgate.com)

## Cylinder Automatic Bollard - Generation 6 Tradition Range

The Generation 6 Line Retractable bollards comply with France's NF P 98.310 standard and are composed of 3 cast structural parts only, which do not wear: the casing, the bollard head and the cover. All bollards in this range may be fitted with a ring of LED's.

### Features

#### Motorization: Electro-pneumatic

- Compressed low-pressure air
- Several bollards can be operated from the same technical centre (one single electric motor = several access points)
- Distance between technical centres/ bollards = up to 800m/ 875 yds
- Environmentally friendly (ISO 14 001 standard)
- Fast motion, lowering and rising of bollard are independently adjustable
- No damage to bollard if vehicle drives over it while it is in motion

#### Dimensions Available/ Materials


- 500mm high x 250mm diameter.....Cast steel
- 600mm high x 250mm diameter.....Cast steel
- 900mm high x 250mm diameter.....Steel

#### Finish

- Zinc coating and powder coat finish available in 6 RAL colours

#### Optional Extras

- Upper limit switch
- Antifreeze heater
- Ring of LED's



Brought to you by Gate Automation Systems (Irl.)

